



INDICATIVE PRODUCT IMAGE

#### **Product file**

Type Compact Mounting Wall

Reference AP50M-1A

Range FA
Version Saddle
Condensation Air
Net weight 48.5 kg
PED 0

Defrost Hot gas
Expansion Capillary
Application MBP
Refrigerant R452A

#### **Dimensions**

 Width L
 400 mm

 Depth P
 796 mm

 Height H
 714 mm

## **Absorptions**

Power consumption 829 W
Current consumption 5.2 A

#### Condenser

Fan-motors no.

 $\begin{array}{cc} \mbox{Diameter} & 254 \mbox{ mm} \\ \mbox{Air flow} & 683 \mbox{ m}^{\rm 3}/\mbox{h} \end{array}$ 

## **Unit cooler**

Fan-motors no. 1

 Diameter
 200 mm

 Air flow
 570 m³/h

 Air throw
 5 m

## Compressor

Type Hermetic


Compressors no.

 Brand
 EMBRACO

 Voltage
 220-240/1/50

 Displacement
 12.12 cm³

## Technical data - AP50M-1A



## Refrigerating capacity table (W) - AP50M-1A - Refrigerant: R452A

TA \ Cold room Temp	-5 °C	0 °C	5 °C
25 °C	945 (7 m³)	1074 (9.3 m³)	1218 (13.9 m³)
32 °C	851 (4 m³)	975 (6 m³)	1107 (9.1 m³)
43 °C	716 (3.3 m³)	826 (4.2 m³)	936 (6 m³)

# Values refered to : Suction gas : +20°C Subcooling : 0K

Superheat: 100% Compressor absorption :

Te -5°C (HBP); Tcond +50°C Te -10°C (MBP); Tcond +50°C Te -30°C (LBP); Tcond +50°C



INDICATIVE PRODUCT IMAGE

## **General features**

- · Self-supporting casing in zinc-plated metal sheet, which is coated with epoxy powder
- Front panel easy to be removed in order to guarantee an easy access to the components and a fast maintenance intervention
- · Hermetic compressors with thermal motor protection
- · Electronic board that can be programmed according to different user requirements

  • Heat exchangers with copper and aluminium blocks

  • Condensation by air (optional by water)

- · Expansion by capillary tube or thermostatic valve
- Automatic defrosting with programmable run, duration and frequency settings"Off cycle defrosting (HBP), and hot gas defrosting (MBP, LBP)."
- · Integral evaporating condensing water tray, or condensing water direct
- discharge
   Electronic card designed for connection in remote management (BMS) and LAN.
- · Cold room light with 2,5m long cable
- · Door micro switch with 2,5m long cable
- Door heater cable for LBP items with 2,5m long cable
- · High pressure switch
- · Evaporating water tray
- Power supply cable (L=2,5m)
  Package included