




10/2020

Mod: DXE8/6/B-S

Production code: IT3813BEDD

	Model	DXE8/6		
	Code Production	IT3813BEDD		
Interface				
				
	Overall Dimension (Width-Depth-Height) *open	mm	724x818x1529(2010*)	
	Packaging Dimension (WxDxH)	mm	760x840x1520	
	Gross weight	Kg	95	
	Net weight	Kg	85	
	Volume	mc	0,98	
	Rack size	mm	500x500	
	Max door /hood opening	mm	450	
	Max glasses/plate Height	mm	440/450	
	General construction		single skin	
	Door/hood Construction		single skin	
	Tank construction		deep drawn	
	Tank volume	liter	15	
	Tank heating element	W	2.100	
	Tank surface strainers		yes-composite	
	Wash pump type		double flow	
	Wash pump power	W	500	
	Wash temperature	°C	55	
	Boiler type		without pressure	
	Boiler volume	liter	6	
	Back-flow system		break tank	
	Boiler heating element	W	6.000	
	Rinse booster pump		YES	
	Rinse booster pump power	W	200	
	Rinse temperature	°C	80	
	Rinse water consumption	Liter /rack	2,6	
	Optimal external water pressure	bar	1-4	
	Drain system		deep drain	
	Drain pump		standard built in	
	Rinse aid dispenser		YES	
	Detergent dispenser		YES	
	Wash cycle	sec	120 - 180 - continuous	
	 Sanitation washing cycle		YES	
	Electric Power	W	6.500	
	Electric Connection	V - ph - Hz	400V 3N 50Hz	
	Fuse	A	16	
	Water softner		NO	
	Plates racks		YES	
	Flat Rack		YES	
	Cutterly Rack		YES	
	Electric cable		YES	
	Drain hose		YES	
	Fill hose		YES	

A		Ø 35 mm M	A	EXIT	Ø 25 mm M
B		G 3/4" M	B	EXIT	G 3/4" F
C		Power supply			



* LUCE UTILE PER CESTELLO
USEFUL SPACE FOR BASKET
LUMIERE UTILE POUR PANIER
NUTZBARE OFFENING FÜR KORBE
ABERTURA UTIL PARA CESTO

Installation layout

Hood type with drain pump

NH50PS 00

