



**MOD : GVL51-G5**

**Production code : 30000033889**

**06/2025**

## Technical data sheet



***GVL51-G5***

### **CHARACTERISTICS**

|                   |            |                   |
|-------------------|------------|-------------------|
| Climate class     |            | : C               |
| Temperature range | (°C)       | : -23 / -18       |
| Power             | ( W )      | : 450W            |
| Voltage/freq.     | ( V / Hz.) | : 220-240v / 50HZ |

### **TECHNICAL SPECIFICATIONS**

|                       |           |                                           |
|-----------------------|-----------|-------------------------------------------|
| External dimensions   | (WXDXH)mm | : 1555*635*890                            |
| Internal dimensions   | (WXDXH)mm | : 1430*510*665                            |
| Package dimensions    | (WXDXH)mm | : 1607*695*891,5                          |
| Gross volume          | (L)       | : 503                                     |
| Net volume            | (L)       | : 436                                     |
| Gross weight          | (kg)      | : 87,4                                    |
| Net weight            | (kg)      | : 78                                      |
| Outer body            |           | : 0.45 mm CRS                             |
| Inner liner           |           | : 0.45 mm pre-painted                     |
| Insulation material   |           | : Rigid P.U.                              |
| Insulation density    |           | : 38~40 kg/m³                             |
| Internal light        |           | : -                                       |
| Canopy light          |           | : -                                       |
| Light Switch          |           | : -                                       |
| Door Switch           |           | : -                                       |
| Levelling leg (front) |           | : N/A                                     |
| Levelling leg (back)  |           | : N/A                                     |
| Roller                |           | : 4 castor                                |
| Comp. capacity        |           | : CUBIGEL 439 W                           |
| Evaporator            |           | : SKIN                                    |
| Evap. ventilator      |           | : NA                                      |
| Condenser             |           | : AUXILLARY AND SKIN                      |
| Cond. ventilator      |           | : AXIAL_220-240V_7/31W_PROPELLER_200MM_34 |
| Thermostat            |           | : MECHANICAL                              |
| Refrigerant           |           | : R290                                    |
| Refrigerant charge    | (g )      | : 120                                     |
| Approvals             |           | : CE,ROHS                                 |

\* External depth is without back stopper.

