


08/2015

Mod: RBB/2+2

Production code: 10401202-0-0-G (V1 2X2)



Diamond
catering equipment

Model	RBB/2	URA/P1	RBB/2+2	RBB/3+3	URB/P2	RBB/4+4
						
Production code	10401201-0-0-G	10402701-0-0-0	10401202-0-0-G	10401204-0-0-G	10402702-0-0-0	10401206-0-0-G
Description	Storage cabin 600L	Cooling unit for Storage cabin 600/850 L	Storage cabin 850L	Storage cabin 1200L	Cooling unit for Storage cabin 1200/1550 L	Storage cabin 1550L
No. and type of doors	2 Full	—	2 Full	2 Full	—	2 Full
No. and type of grid shelves	—	—	—	—	—	—
Light	no	—	no	no	—	no
Key lock	no	—	no	no	—	no
Range (°C)	—	+2° +8°	—	—	+2° +8°	—
Operating Mode	—	Ventilated	—	—	Ventilated	—
External Dimensions						
Width (mm)	1060	675	1060	1465	675	1870
Depth/with open doors (mm)	730 / 1205	495	995 / 1470	995 / 1670	495	995 / 1872
Height (mm)	1060	305	1060	1060	305	1060
Internal Dimensions						
Width (mm)	980	—	980	1385	—	1790
Depth (mm)	620	—	885	885	—	885
Height (mm)	980	—	980	980	—	980
Gross capacity (L)	720	—	1000	1400	—	1800
Defrost						
Type of defrost	—	By time	—	—	By time	—
No. of defrost in 24h	—	6	—	—	6	—
Evaporation of defrost water	—	Hot gas	—	—	Hot gas	—
Compressor						
Brand	—	Tecumseh	—	—	Tecumseh	—
Model	—	AE 4425 Y	—	—	AE 4430 Y	—
Power (hp)	—	—	—	—	—	—
Cooling power (W)	—	352	—	—	445	—
Evaporation temp. (°C)	—	-15	—	—	-15	—
Climate class (°C)	—	+32	—	—	+43	—
Refrigerant						
Type	—	R134a	—	—	R134a	—
Refrigerant quantity (g)	—	210	—	—	250	—
Electronic Controller						
Brand	—	Dixell	—	—	Dixell	—
Model	—	XR30CH	—	—	XR30CH	—
Electrical						
Power input (W/A)	—	260 / 2,05	—	—	360 / 2,80	—
Power supply (V/Hz)	—	230/50	—	—	230/50	—
220V/60Hz	—	no	—	—	no	—
Packaging Details						
Packed volume (m³)	0,60	0,17	0,60	0,81	0,17	1,02
Gross weight (kg)	92	29	105	126	30	156
Net weight (kg)	62	25	75	96	26	123