


08/2015

Mod: SY160G/PM

Production code: 10107719-0-0-0 (L9)



Diamond
catering equipment

Model	SX132G/CM	SX175G/CM	SX219G/CM	SX160G/PM	SX198G/PM	SX249G/PM	SY160G/PM	SY198G/PM	SY249G/PM
									
Production code	10107711-0-0-A	10107712-0-0-A	10107713-0-0-A	10107710-0-0-0	10107707-0-0-0	10107708-0-0-0	10107719-0-0-0	10107716-0-0-0	10107717-0-0-0
Description	GN1/4 topping shelf with SS lid	GN1/4 topping shelf with SS lid	GN1/4 topping shelf with SS lid	GN1/4 topping shelf with glass top	GN1/4 topping shelf with glass top	GN1/4 topping shelf with glass top	GN1/3 topping shelf with glass top	GN1/3 topping shelf with glass top	GN1/3 topping shelf with glass top
Range (°C)	0° + 8°	0° + 8°	0° + 8°	0° + 8°	0° + 8°	0° + 8°	0° + 8°	0° + 8°	0° + 8°
Operating Mode	Static	Static	Static	Static	Static	Static	Static	Static	Static
External Dimensions									
Width (mm)	1320	1755	2190	1600	1980	2490	1600	1980	2490
Depth (mm)	324	324	324	324	324	324	384	384	384
Height (mm)	250 / 510	250 / 510	250 / 510	387	387	387	387	387	387
Internal Dimensions									
Width (mm)	837	1272	1707	1117	1497	2007	1117	1497	2007
Depth (mm)	243	243	243	243	243	243	303	303	303
Height (mm)	150	150	150	150	150	150	150	150	150
Gross capacity (L)	31	46	62	41	55	73	51	68	91
Defrost									
Type of defrost	Automatic by time, stop compressor	Automatic by time, stop compressor	Automatic by time, stop compressor	Automatic by time, stop compressor	Automatic by time, stop compressor	Automatic by time, stop compressor	Automatic by time, stop compressor	Automatic by time, stop compressor	Automatic by time, stop compressor
Compressor									
Brand	Tecumseh	Tecumseh	Tecumseh	Tecumseh	Tecumseh	Tecumseh	Tecumseh	Tecumseh	Tecumseh
Model	THB 4415 Y	THB 4415 Y	THB 4419 Y	THB 4415 Y	THB 4415 Y	THB 4419 Y	THB 4415 Y	THB 4415 Y	THB 4419 Y
Power (hp)	1/8	1/8	1/6	1/8	1/8	1/6	1/8	1/8	1/6
Cooling power (W)	216	216	263	216	216	263	216	216	263
Evaporation temp. (°C)	-15	-15	-15	-15	-15	-15	-15	-15	-15
Climate class (°C)	+43	+43	+43	+43	+43	+43	+43	+43	+43
Refrigerant									
Type	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a	R134a
Quantity (g)	200	200	375	200	200	375	200	225	375
Electronic Controller									
Brand	Dixell	Dixell	Dixell	Dixell	Dixell	Dixell	Dixell	Dixell	Dixell
Model	XR20CH	XR20CH	XR20CH	XR20CH	XR20CH	XR20CH	XR20CH	XR20CH	XR20CH
Electrical									
Power input (W/A)	170 / 1,27	170 / 1,27	190 / 1,4	170 / 1,27	170 / 1,27	190 / 1,4	170 / 1,27	170 / 1,27	190 / 1,4
Power supply (V/Hz)	220-230/50	220-230/50	220-230/50	220-230/50	220-230/50	220-230/50	220-230/50	220-230/50	220-230/50
220V/60Hz	no	no	no	no	no	no	no	no	no
Packaging Details									
Packed volume (m³)	0,18	0,24	0,29	0,22	0,27	0,35	0,27	0,33	0,43
Gross weight (kg)	44	54	65	66	72	95	69	77	100
Net weight (kg)	32	39	46	53	57	76	55	62	82