09/2015

Mod: TAURO-NEW/B

Production code: M1105



FABRICANTES DE MOLINOS DE CAFÉ

MANUFACTURERS OF COFFEE GRINDERS Molino de café profesional para todo tipo de cafés

Professional coffee grinder for all types of coffee.



COLLECTION CLASSIC

TECHNICAL CHARACTERISTICS 0-500gr/6' Max 2Kg

Voltage: 230V / 220V / 110V Frequency: 50Hz / 60Hz Phases: 1(monophase) RPM: 1.300 / 1.600 Current: 1,4A / 3A Capacitor: 9nf / 40nf Power: 0.12Hp / 275W Protection rating: IP21 Motor supplied with thermal protector Maximum operating time: 30 min. Tempered steel grinding wheel (62HRc) Ø 60mm

Lifespan of grinding wheels: 500kg

Hopper capacity: 1kg

Doser capacity: 600g

Doser regulation: 5/12g

Doser lever: right/left

Stop/start standard version: manual

Dimensions width x length x height: 180x310x560mm

Weight: 9kg

Air noise: 77dB

Diseñado bajo directiva 89/392 CE.






(62HRc) ø 60mm



Grinding blades in tempered steel



310mm















MAIN ATTRIBUTES

Hopper (1kg) made of unbreakable and non-deformable material (co.polyester), with fast lock system and self-levelling when off the coffee grinder, with the possibility of cleaning in a dishwasher at 90 °C. Micrometric regulation of the coffee grind using a regulatory pawl. New expulsion system for the ground coffee (always leaving the grinding cavity clean when the coffee grinder stops). Bodywork made of stainless steel, with ventilation system (internal air inlet and outlet). Tray integrated into the bodywork, with ground coffee sweeping system. Single-bodied, hermetically sealed doser without aroma loss, vibrationless and made of unbreakable material. Ergonomic handle. Universal coffee tamper (rotatable). Doser fitted with gasket-saver (portafilter positioner). Hardened steel grinding blades (62/65 HRc) 60mm in diameter.

Optional: Left- or right-handed doser lever. Coffee counter. Optional customisation system on the doser in chrome plate.

