


01/2020



Mod: TG4N/HGX-R2


Production code: TEMG4V2510-DM (GR.SINISTRA)

	Modello - Model Model - Gerätetyp				TG2N/HA-R2	Code Production	TEMG2V2520-DM
					TG2N/H-R2	Code Production	TEMG2V2510-DM
							
	Descrizione - Description - Description - Beschreibung				2 Doors		
	Tipo di teglie - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes				GN 1/1		
	Range				-2°C...+8°C		
	Scheda Elettronica - Electronic card				EVCO EVX214		
	Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus S = Statico-Static-Statique-Stille Kühlung V = Ventilato-Ventilated-Ventile-Umluftkühlung				V		
	Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen			I	226		
	Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen						
	Lunghezza - Width -Largeur - Breite			mm	1355		
	Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tü			mm	700/1090		
	Altezza - Height - Hauteur - Höhe			mm	850		
	Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen						
	Lunghezza - Width -Largeur - Breite			mm	791		
	Profondità - Depth - Profondeur - Tiefe			mm	530		
	Altezza - Height - Hauteur - Höhe			mm	540		
	Porte - Doors - Portes - Türen				2		
	Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung				GN 1/1 Griglia plastificata - Plastic-Coated Grid Grille Plastifiee - Kunststoff-Beschichtetes Gitter		
					2		
	Serratura - Lock - Serrure - Schloss						
	Fondo inox - Stainless Steel bottom - Fond inox - Edelstahlgrundboden						
	Sbrinamento - Defrost - Dégivrages - Abtauen						
	Type				Gas caldo - Hot gas - Gaz chaude - Heissem Gas		
	N° Defrost in 24 hrs.				3		
	Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung				Gas caldo - Hot gas - Gaz chaude - Heissem Gas		
	Compressor 						
	Model				EMC3119U		
	Potenza - Power - Puissance - Leistung			Hp	1/4		
	Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung			watt	425		
	Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp			Type	R290		
	Quantità di refrigerante - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge			gr	80		
	Potenza assorbita - Total Power - Puissance - Leistung			watt	250W - 1A		
	Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung			V	230V~ 50Hz		
	Peso Netto - Net weight - Poids net - Netto Gewicht			kg	163		
	Volume - Volume - Volume - Volumen			mc	1,07		
	Efficienza Energetica - Energy Efficiency - Classe Énergie - Energieeffizienzklasse				A		
	Energia - Energy - Énergie - Energie			kWh / annum	554		
	Volume Netto - Net Volume - Volume Net - Nettoinhalt			I	204		
	Classe Climatica - Climate Class - Classe Climatique - Klima Klasse				5 +40°C 40%		

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung ☐ =Optional








	Modello - Model Model - Gerätetyp			TG3N/HA-R2	
				Code Production	TEMG3V2520-DM
				TG3N/H-R2	
			Code Production	TEMG3V2510-DM	
					
				3 Doors	
				GN 1/1	
				-2°C...+8°C	
				EVCO EVX214	
				V	
				355	
				1805	
				700/1090	
				850	
				1239	
				530	
				540	
				3	
				GN 1/1 Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter	
				3	
					
					
				Gas caldo - Hot gas - Gaz chaude - Heissem Gas	
				3	
				Gas caldo - Hot gas - Gaz chaude - Heissem Gas	
				EMC3119U	
				1/4	
				425	
				R290	
				80	
				250W - 1A	
				230V~ 50Hz	
				206	
				1,42	
				A	
				621	
				319	
				5 +40°C 40%	

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung

 =Optional

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung ☐ = Optional








	Modello - Model Model - Gerätetyp				TG4N/HA-R2
			Code Production TEMG4V2520-DM		
			TG4N/H-R2		
		Code Production TEMG4V2510-DM			
					4 Doors
					GN 1/1
					-2°C...+8°C
					EVCO EVX214
					V
					483
					2250
					700/1090
					850
					1687
					530
					540
					4
					GN 1/1 Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter
					4
					
					
					Gas caldo - Hot gas - Gaz chaude - Heissem Gas
					3
					Gas caldo - Hot gas - Gaz chaude - Heissem Gas
					EMC3119U
					1/4
					425
					R290
					80
					250W - 1A
					230V~ 50Hz
					248
					1,76
					A
					687
					433
					5 +40°C 40%

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung

 = Optional

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung  = Optional









↙ Modello - Model Model - Gerätetyp			TS2N/HA Code ProductionTEPG2V1520-DM TS2N/H Code ProductionTEPG2V1510-DM	
				
► Descrizione - Description - Description - Beschreibung			2 Doors	
Tipo di teglie - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes			GN 1/1	
🔥 Range			-2°C...+8°C	
📄 Scheda Elettronica - Electronic card			CAREL PJEZ	
🌀 Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus S = Statico-Static-Statique-Stille Kühlung V = Ventilato-Ventilated-Ventile-Umluftkühlung			V	
📏 Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen I			226	
↕ Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen				
Lunghezza - Width -Largeur - Breite mm			1145	
Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tü mm			700/1090	
Altezza - Height - Hauteur - Höhe mm			850	
↕ Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen				
Lunghezza - Width -Largeur - Breite mm			791	
Profondità - Depth - Profondeur - Tiefe mm			530	
Altezza - Height - Hauteur - Höhe mm			540	
↘ Porte - Doors - Portes - Türen			2	
🔒 Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung			GN 1/1 Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter	
🔒 Serratura - Lock - Serrure - Schloss			☐	
🔒 Fondo inox - Stainless Steel bottom - Fond inox - Edelstahlgrundboden			☐	
🔒 Sbrinamento - Defrost - Dégivrages - Abtauen				
Type			Elettrico - Electric - Electrique - Elektrische	
N° Defrost in 24 hrs.			3	
Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung			Elettrico - Electric - Electrique - Elektrische	
🔒 Compressor				
Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung watt			550W (@-10°C / +45°C)	
↘ Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp Type			R134a	
↘ Classe Climatica - Climate Class - Classe Climatique - Klima Classe			5 +40°C 40%	
⚡ Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung V			220-240V~ 50/60Hz	
⚖ Peso Netto - Net weight - Poids net - Netto Gewicht kg			116	
Volume - Volume - Volume - Volumen mc			0,91	

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung

□ = Optional








↘ Modello - Model Model - Gerätetyp					TS3N/HA Code ProductionTEPG3V1520-DM TS3N/H Code ProductionTEPG3V1510-DM	
► Descrizione - Description - Description - Beschreibung					3 Doors	
Tipo di teglie - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes					GN 1/1	
🔥 Range					-2°C...+8°C	
📄 Scheda Elettronica - Electronic card					CAREL PJEZ	
🌀 Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus S = Statico-Static-Statique-Stille Kühlung V = Ventilato-Ventilated-Ventile-Umluftkühlung					V	
📏 Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen I					355	
↕ Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen					1595	
Lunghezza - Width -Largeur - Breite mm					700/1090	
Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tü mm					850	
Altezza - Height - Hauteur - Höhe mm						
↕ Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen					1239	
Lunghezza - Width -Largeur - Breite mm					530	
Profondità - Depth - Profondeur - Tiefe mm					540	
Altezza - Height - Hauteur - Höhe mm					3	
↘ Porte - Doors - Portes - Türen					GN 1/1 Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter	
🔒 Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung					3	
🔒 Serratura - Lock - Serrure - Schloss					📏	
📏 Fondo inox - Stainless Steel bottom - Fond inox - Edelstahlgrundboden					📏	
🧊 Sbrinamento - Defrost - Dégivrages - Abtauen					Elettrico - Electric - Electrique - Elektrische	
Type					3	
N° Defrost in 24 hrs.					Elettrico - Electric - Electrique - Elektrische	
Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung						
🔧 Compressor					550W (@-10°C / +45°C)	
Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung watt					R134a	
↘ Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp Type					5 +40°C 40%	
↘ Classe Climatica - Climate Class - Classe Climatique - Klima Classe					220-240V~ 50/60Hz	
⚡ Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung V					154	
⚖ Peso Netto - Net weight - Poids net - Netto Gewicht kg					1,26	
Volume - Volume - Volume - Volumen mc						

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung

□ = Optional










	Modello - Model Model - Gerätetyp			TS4N/HA	
				Code Production	TEPG4V1520-DM
				TS4N/H	
				Code Production	TEPG4V1510-DM
					
	Descrizione - Description - Description - Beschreibung		4 Doors		
	Tipo di teglie - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes		GN 1/1		
	Range		-2°C...+8°C		
	Scheda Elettronica - Electronic card		CAREL PJEZ		
	Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus S = Statico-Static-Statique-Stille Kühlung V = Ventilato-Ventilated-Ventile-Umluftkühlung		V		
	Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen	l	483		
	Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen				
	Lunghezza - Width -Largeur - Breite	mm	2040		
	Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tü	mm	700/1090		
	Altezza - Height - Hauteur - Höhe	mm	850		
	Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen				
	Lunghezza - Width -Largeur - Breite	mm	1687		
	Profondità - Depth - Profondeur - Tiefe	mm	530		
	Altezza - Height - Hauteur - Höhe	mm	540		
	Porte - Doors - Portes - Türen		4		
	Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung		GN 1/1 Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter 4		
	Serratura - Lock - Serrure - Schloss				
	Fondo inox - Stainless Steel bottom - Fond inox - Edelstahlgrundboden				
	Sbrinamento - Defrost - Dégivrages - Abtauen				
	Type		Elettrico - Electric - Electrique - Elektrische		
	N° Defrost in 24 hrs.		3		
	Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung		Elettrico - Electric - Electrique - Elektrische		
	Compressor				
	Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung	watt	550W (@-10°C / +45°C)		
	Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp	Type	R134a		
	Classe Climatica - Climate Class - Classe Climatique - Klima Classe		5 +40°C 40%		
	Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung	V	220-240V~ 50/60Hz		
	Peso Netto - Net weight - Poids net - Netto Gewicht	kg	190		
	Volume - Volume - Volume - Volumen	mc	1,6		

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung


□ = Optional







	Modello - Model Model - Gerätetyp		TG2B/HA-R2	
			Code Production	TEMG2V2540-DM
			TG2B/H-R2	
			Code Production	TEMG2V2530-DM
				
	Descrizione - Description - Description - Beschreibung		2 Doors	
	Tipo di teglie - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes		GN 1/1	
	Range		-20°C...-10°C	
	Scheda Elettronica - Electronic card		EVCO EVX214	
	Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus S = Statico-Static-Statique-Stille Kühlung V = Ventilato-Ventilated-Ventile-Umluftkühlung		V	
	Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen		I	226
	Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen			
	Lunghezza - Width -Largeur - Breite	mm		1355
	Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tü	mm		700/1090
	Altezza - Height - Hauteur - Höhe	mm		850
	Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen			
	Lunghezza - Width -Largeur - Breite	mm		791
	Profondità - Depth - Profondeur - Tiefe	mm		530
	Altezza - Height - Hauteur - Höhe	mm		540
	Porte - Doors - Portes - Türen			2
	Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung		Griglia plastificata - Plastic-Coated Grid Grille Plastifée - Kunststoff-Beschichtetes Gitter GN 1/1 2	
	Serratura - Lock - Serrure - Schloss			☐
	Fondo inox - Stainless Steel bottom - Fond inox - Edelstahlgrundboden			☐
	Sbrinamento - Defrost - Dégivrage - Abtauen			
	Type		Gas caldo - Hot gas - Gaz chaude - Heissem Gas	
	N° Defrost in 24 hrs.		4	
	Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung		Gas caldo - Hot gas - Gaz chaude - Heissem Gas	
	Compressor			
	Model		NEU6217U	
	Potenza - Power - Puissance - Leistung	Hp	3/4	
	Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung	watt	520	
		Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp	Type	R290
	Quantità di refrigerante - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge	gr	120	
	Potenza assorbita - Total Power - Puissance - Leistung	watt	500W -2,5A (700W - 3,5A)	
	Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung	V	230V~ 50Hz	
	Peso Netto - Net weight - Poids net - Netto Gewicht	kg	153	
	Volume - Volume - Volume - Volumen	mc	1,07	
	Efficienza Energetica - Energy Efficiency - Classe Énergie - Energieeffizienzklasse		D	
	Energia - Energy - Énergie - Energie	kWh / annum	2485	
	Volume Netto - Net Volume - Volume Net - Nettoinhalt	I	204	
	Classe Climatica - Climate Class - Classe Climatique - Klima Classe		5 +40°C 40%	


● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung □ = Optional







	Modello - Model Model - Gerätetyp			TG3B/HA-R2	
				Code Production	TEMG3V2540-DM
				TG3B/H-R2	
				Code Production	TEMG3V2530-DM
					
	Descrizione - Description - Description - Beschreibung			3 Doors	
	Tipo di teglie - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes			GN 1/1	
	Range			-20°C...-10°C	
	Scheda Elettronica - Electronic card			EVCO EVX214	
	Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus S = Statico-Static-Statique-Stille Kühlung V = Ventilato-Ventilated-Ventile-Umluftkühlung			V	
		Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen	l	355	
	Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen				
	Lunghezza - Width -Largeur - Breite		mm	1805	
	Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tü		mm	700/1090	
	Altezza - Height - Hauteur - Höhe		mm	850	
	Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen				
	Lunghezza - Width -Largeur - Breite		mm	1239	
	Profondità - Depth - Profondeur - Tiefe		mm	530	
	Altezza - Height - Hauteur - Höhe		mm	540	
	Porte - Doors - Portes - Türen			3	
	Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung			Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter GN 1/1 3	
	Serratura - Lock - Serrure - Schloss			☐	
	Fondo inox - Stainless Steel bottom - Fond inox - Edelstahlgrundboden			☐	
	Sbrinamento - Defrost - Dégivrages - Abtauen				
	Type			Gas caldo - Hot gas - Gaz chaude - Heissem Gas	
	N° Defrost in 24 hrs.			4	
	Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung			Gas caldo - Hot gas - Gaz chaude - Heissem Gas	
	Compressor 				
	Model			NEU2168U	
	Potenza - Power - Puissance - Leistung	Hp		3/4	
	Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung	watt		600	
	Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp		Type	R290	
	Quantità di refrigerante - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge		gr	120	
	Potenza assorbita - Total Power - Puissance - Leistung		watt	660W-3,3A (950W-4,6A)	
	Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung		V	230V~ 50Hz	
	Peso Netto - Net weight - Poids net - Netto Gewicht		kg	206	
	Volume - Volume - Volume - Volumen		mc	1,42	
	Efficienza Energetica - Energy Efficiency - Classe Énergie - Energieeffizienzklasse			D	
	Energia - Energy - Énergie - Energie		kWh / annum	3050	
	Volume Netto - Net Volume - Volume Net - Nettoinhalt		l	319	
	Classe Climatica - Climate Class - Classe Climatique - Klima Klasse			5 +40°C 40%	


● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung □ = Optional







	Modello - Model Model - Gerätetyp		TG4B/HA-R2	
			Code Production	TEMG4V2540-DM
			TG4B/H-R2	
			Code Production	TEMG4V2530-DM
				
	Descrizione - Description - Description - Beschreibung		4 Doors	
	Tipo di teglie - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes		GN 1/1	
	Range		-20°C...-10°C	
	Scheda Elettronica - Electronic card		EVCO EVX214	
	Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus S = Statico-Static-Statique-Stille Kühlung V = Ventilato-Ventilated-Ventile-Umluftkühlung		V	
	Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen		I	483
	Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen			
	Lunghezza - Width -Largeur - Breite	mm		2250
	Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tü	mm		700/1090
	Altezza - Height - Hauteur - Höhe	mm		850
	Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen			
	Lunghezza - Width -Largeur - Breite	mm		1687
	Profondità - Depth - Profondeur - Tiefe	mm		530
	Altezza - Height - Hauteur - Höhe	mm		540
	Porte - Doors - Portes - Türen			4
	Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung		Griglia plastificata - Plastic-Coated Grid Grille Plastifée - Kunststoff-Beschichtetes Gitter GN 1/1 4	
	Serratura - Lock - Serrure - Schloss			☐
	Fondo inox - Stainless Steel bottom - Fond inox - Edelstahlgrundboden			☐
	Sbrinamento - Defrost - Dégivrage - Abtauen			
	Type		Gas caldo - Hot gas - Gaz chaude - Heissem Gas	
	N° Defrost in 24 hrs.		4	
	Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung		Gas caldo - Hot gas - Gaz chaude - Heissem Gas	
	Compressor			
	Model		NEU2168U	
	Potenza - Power - Puissance - Leistung	Hp	3/4	
	Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung	watt	600	
		Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp	Type	R290
	Quantità di refrigerante - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge	gr	120	
	Potenza assorbita - Total Power - Puissance - Leistung	watt	660W-3,3A (950W-4,6A)	
	Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung	V	230V~ 50Hz	
	Peso Netto - Net weight - Poids net - Netto Gewicht	kg	248	
	Volume - Volume - Volume - Volumen	mc	1,76	
	Efficienza Energetica - Energy Efficiency - Classe Énergie - Energieeffizienzklasse		D	
	Energia - Energy - Énergie - Energie	kWh / annum	3607	
	Volume Netto - Net Volume - Volume Net - Nettoinhalt	I	433	
	Classe Climatica - Climate Class - Classe Climatique - Klima Classe		5 +40°C 40%	

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung ☐ = Optional









	Modello - Model Model - Gerätetyp		TS2B/HA	
			Code Production	TEPG2V1550-DM
			TS2B/H	
			Code Production	TEPG2V1540-DM
				
	Descrizione - Description - Description - Beschreibung		2 Doors	
	Tipo di teglie - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes		GN 1/1	
	Range		-20°C...-10°C	
	Scheda Elettronica - Electronic card		CAREL PJEZ	
	Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus S = Statico-Static-Statique-Stille Kühlung V = Ventilato-Ventilated-Ventile-Umluftkühlung		V	
	Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen	l	226	
	Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen			
	Lunghezza - Width -Largeur - Breite	mm	1145	
	Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tü	mm	700/1090	
	Altezza - Height - Hauteur - Höhe	mm	850	
	Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen			
	Lunghezza - Width -Largeur - Breite	mm	791	
	Profondità - Depth - Profondeur - Tiefe	mm	530	
	Altezza - Height - Hauteur - Höhe	mm	540	
	Porte - Doors - Portes - Türen		2	
	Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung		GN 1/1 Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter 2	
	Serratura - Lock - Serrure - Schloss		☐	
	Fondo inox - Stainless Steel bottom - Fond inox - Edelstahlgrundboden		☐	
	Sbrinamento - Defrost - Dégivrages - Abtauen			
	Type		Elettrico - Electric - Electrique - Elektrische	
	N° Defrost in 24 hrs.		3	
	Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung		Elettrico - Electric - Electrique - Elektrische	
	Compressor			
	Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung	watt	520 (@-30°C / +45°C)	
	Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp	Type	R404A/R452A	
	Classe Climatica - Climate Class - Classe Climatique - Klima Classe		5 +40°C 40%	
	Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung	V	220-240V~ 50/60Hz	
	Peso Netto - Net weight - Poids net - Netto Gewicht	kg	116	
	Volume - Volume - Volume - Volumen	mc	0,91	

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung

□ = Optional








	Modello - Model Model - Gerätetyp		TS3B/HA	
			Code Production	TEPG3V1550-DM
			TS3B/H	
			Code Production	TEPG3V1540-DM
				
	Descrizione - Description - Description - Beschreibung		3 Doors	
	Tipo di teglie - Trays type - Type de plateaux - Blechetyt - Tipo de fuentes		GN 1/1	
	Range		-20°C...-10°C	
	Scheda Elettronica - Electronic card		CAREL PJEZ	
	Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus S = Statico-Static-Statique-Stille Kühlung V = Ventilato-Ventilated-Ventile-Umluftkühlung		V	
	Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen	l	355	
	Dimensioni esterne - External Dimension - Dimensions externes - außenabmessungen			
	Lunghezza - Width -Largeur - Breite	mm	1595	
	Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tü	mm	700/1090	
	Altezza - Height - Hauteur - Höhe	mm	850	
	Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen			
	Lunghezza - Width -Largeur - Breite	mm	1239	
	Profondità - Depth - Profondeur - Tiefe	mm	530	
	Altezza - Height - Hauteur - Höhe	mm	540	
	Porte - Doors - Portes - Türen		3	
	Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung		GN 1/1 Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter 3	
	Serratura - Lock - Serrure - Schloss		☐	
	Fondo inox - Stainless Steel bottom - Fond inox - Edelstahlgrundboden		☐	
	Sbrinamento - Defrost - Dégivrages - Abtauen			
	Type		Elettrico - Electric - Electrique - Elektrische	
	N° Defrost in 24 hrs.		3	
	Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung		Elettrico - Electric - Electrique - Elektrische	
	Compressor			
	Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung	watt	610 (@-30°C / +45°C)	
	Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp	Type	R404A/R452A	
	Classe Climatica - Climate Class - Classe Climatique - Klima Classe		5 +40°C 40%	
	Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung	V	220-240V~ 50/60Hz	
	Peso Netto - Net weight - Poids net - Netto Gewicht		kg	154
	Volume - Volume - Volume - Volumen		mc	1,26

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung

□ = Optional





	Modello - Model Model - Gerätetyp		TS4B/HA	
			Code Production	TEPG4V1550-DM
			TS4B/H	
			Code Production	TEPG4V1540-DM
				
	Descrizione - Description - Description - Beschreibung		4 Doors	
	Tipo di teglie - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes		GN 1/1	
	Range		-20°C...-10°C	
	Scheda Elettronica - Electronic card		CAREL PJEZ	
	Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus S = Statico-Static-Statique-Stille Kühlung V = Ventilato-Ventilated-Ventile-Umluftkühlung		V	
	Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen	l	483	
	Dimensioni esterne - External Dimension - Dimensions externes - außenabmessungen			
	Lunghezza - Width -Largeur - Breite	mm	2040	
	Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tür	mm	700/1090	
	Altezza - Height - Hauteur - Höhe	mm	850	
	Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen			
	Lunghezza - Width -Largeur - Breite	mm	1687	
	Profondità - Depth - Profondeur - Tiefe	mm	530	
	Altezza - Height - Hauteur - Höhe	mm	540	
	Porte - Doors - Portes - Türen		4	
	Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung		GN 1/1 Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter 4	
	Serratura - Lock - Serrure - Schloss			
	Fondo inox - Stainless Steel bottom - Fond inox - Edelstahlgrundboden			
	Sbrinamento - Defrost - Dégivrage - Abtauen			
	Type		Elettrico - Electric - Electrique - Elektrische	
	N° Defrost in 24 hrs.		3	
	Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung		Elettrico - Electric - Electrique - Elektrische	
	Compressor			
	Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung	watt	610 (@-30°C / +45°C)	
	Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp	Type	R404A/R452A	
	Classe Climatica - Climate Class - Classe Climatique - Klima Klasse		5 +40°C 40%	
	Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung	V	220-240V~ 50/60Hz	
	Peso Netto - Net weight - Poids net - Netto Gewicht		kg	190
	Volume - Volume - Volume - Volumen		mc	1,6

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung

□ = Optional

