



MOD : CBT51/R2

Production code : LF05TE-M24TR

07/2025

Fiche technique / Scheda tecnica / Ficha técnica / Technisches Datenblatt /
Technical datasheet / Technisch gegevensblad



Dati tecnici

Technical Data

DIMENSIONI (L x P x H)	DIMENSIONS (L x P x H)	790 x 700 x 875 mm
CON IMBALLO (L x P x H)	WITH EMBALLAGE (L x P x H)	810 x 720 x 1020 mm
LARGHEZZA LUCE PORTA	WIDTH DOOR LIGHT	680 mm
ALTEZZA LUCE PORTA	HEIGHT DOOR LIGHT	380 mm
PROFONDITÀ INTERNA	INTERIOR DEPTH	415 mm
SPESSORE	THICKNESS	60 mm
CLASSE CLIMATICA	CLIMATE CLASS	4
CAPACITÀ ABBATTIMENTO	BLAST CHILLING CAPACITY	18 Kg
CAPACITÀ CONGELAMENTO	FREEZING CAPACITY	12 Kg
CAPACITÀ REFRIGERAZIONE ¹	REFRIGERATION CAPACITY ¹	1416 W
POTENZA ELETTRICA	POWER INPUT	815 W
ALLESTIMENTO CATERING	CATERING LAYOUT	5 GN1/1
ALLESTIMENTO BAKING	BAKING LAYOUT	5 EN 600x400
PASSO TEGLIE	PAN CLEARANCE	65 mm
PESO NETTO	NET WEIGHT	75 Kg
PESO LORDO	GROSS WEIGHT	100 Kg
CAVO ELETTRICO	POWER CABLE	16A EU PLUG
ALIMENTAZIONE ELETTRICA	POWER SUPPLY	230 v - 1/50 Hz
TUBO SCARICO ACQUA	DRAINAGE HOSE	Ø ½"
CONTROLLO CICLO: A TEMPO	CYCLE CONTROL: TIMED	Si
CONTROLLO CICLO: A SPILLONE	CYCLE CONTROL: SENSOR PROBE	Si
CORPO ESTERNO	EXTERIOR	AISI 304 finitura SB
INGOMBRO	ENCUMBRANCE	0.6 m3

¹ Temp. evap. -10°C, temp. cond. +45°C / Evap. temp. -10°C, cond. temp. +45°C

