



MOD : DEC-60

Production code : 9996ZP900SEL

10/2023

Idroestrattori ZP
Hydro Extractor ZP
Hidroextractores ZP
Sleudern ZP
Центрифуги ZP
Hydro Extracteur ZP



	DEC-8	DEC-12	DEC-20	DEC-30	DEC-60
Carico massimo [kg]	8	12	20	30	57
Giri al minuto [r.p.m.]	1450	1450	1450	1000	1100
Fattore G	438	493	696	408	609
Diametro cestello [mm]	400	450	635	730	900
Altezza cestello [mm]	300	350	350	350	500
Volume cestello [litri]	34	42	95	120	300
Larghezza [mm]	540	610	830	980	1350
Profondità [mm]	750	800	990	1150	1740
Altezza [mm]	800	1000	1000	1050	1000
Peso netto [kg]	95	144	295	360	1200
Peso lordo [kg]	110	164	330	400	1300
Volume [m ³]	0.44	0.64	1.32	1.64	2.85
Motore azionamento [kW]	1.1	2.2	4.0	5.5	7.5
Assorbimento elettrico [A] 3 x 400V + T allo spunto	6.0	8.0	14.0	30.0	33
Assorbimento elettrico [A] 3 x 400V + T a regime	1.3	1.8	1.4	2.8	4.0
Assorbimento elettrico [A] 3 x 230V + T allo spunto	10.4	13.8	24.2	31.2	57.0
Assorbimento elettrico [A] 3 x 230V + T a regime	2.3	3.1	2.4	2.6	7.0
Carico dinamico [kg/cm ²]	3.1	3.5	3	3	2.5

	DEC-8	DEC-12	DEC-20	DEC-30	DEC-60
Maximum loading [kg]	8	12	20	30	57
Round per Minute [r.p.m.]	1450	1450	1450	1000	1100
G Factor	438	493	696	408	609
Drum diameter [mm]	400	450	635	730	900
Drum height [mm]	300	350	350	350	500
Drum volume [litri]	34	42	95	120	300
Width [mm]	540	610	830	980	1350
Depth [mm]	750	800	990	1150	1740
Height [mm]	800	1000	1000	1050	1000
Net weight [kg]	95	144	295	360	1200
Gross weight [kg]	110	164	330	400	1300
Volume [m ³]	0.44	0.64	1.32	1.64	2.85
Working Motor [kW]	1.1	2.2	4.0	5.5	7.5
Electric absorbtion [A] 3 x 400V + T Pickup	6.0	8.0	14.0	30.0	33
Electric absorbtion [A] 3 x 400V + T working	1.3	1.8	1.4	2.8	4.0
Electric absorbtion [A] 3 x 230V + T Pickup	10.4	13.8	24.2	31.2	57.0
Electric absorbtion [A] 3 x 230V + T working	2.3	3.1	2.4	2.6	7.0
Dynamic load [kg/cm ²]	3.1	3.5	3	3	2.5



	DEC-8	DEC-12	DEC-20	DEC-30	DEC-60
Carga Maxima [kg]	8	12	20	30	57
Vuelta al minuto [r.p.m.]	1450	1450	1450	1000	1100
Factor G	438	493	696	408	609
Diametro Cesto [mm]	400	450	635	730	900
Altura cesto [mm]	300	350	350	350	500
Volume cesto [litros]	34	42	95	120	300
Anchura [mm]	540	610	830	980	1350
Profundidad [mm]	750	800	990	1150	1740
Altura [mm]	800	1000	1000	1050	1000
Peso neto [kg]	95	144	295	360	1200
Peso lordo [kg]	110	164	330	400	1300
Volumen [m ³]	0.44	0.64	1.32	1.64	2.85
Motor accionamiento [kW]	1.1	2.2	4.0	5.5	7.5
Absorción electrica [A] 3 x 400V + T al punto de arranque	6.0	8.0	14.0	30.0	33
Absorción electrica [A] 3 x 400V + T a régimen	1.3	1.8	1.4	2.8	4.0
Absorción electrica [A] 3 x 230V + T al punto de arranque	10.4	13.8	24.2	31.2	57.0
Absorción electrica [A] 3 x 230V + T a régimen	2.3	3.1	2.4	2.6	7.0
Carga dinamica [kg/cm ²]	3.1	3.5	3	3	2.5



	DEC-8	DEC-12	DEC-20	DEC-30	DEC-60
Füllgewicht [kg]	8	12	20	30	57
R.P.M.	1450	1450	1450	1000	1100
G Faktor	438	493	696	408	609
Trommel Durchmesser [mm]	400	450	635	730	900
Trommel Höhe [mm]	300	350	350	350	500
Trommel Volumen [litri]	34	42	95	120	300
Breite [mm]	540	610	830	980	1350
Tiefe [mm]	750	800	990	1150	1740
Höhe [mm]	800	1000	1000	1050	1000
Nettogewicht [kg]	95	144	295	360	1200
Bruttogewicht [kg]	110	164	330	400	1300
Volumen [m ³]	0.44	0.64	1.32	1.64	2.85
Motor [kW]	1.1	2.2	4.0	5.5	7.5
Elektrischer Bedarf [A] 3 x 400V + T an Anlasstoss	6.0	8.0	14.0	30.0	33
Elektrischer Bedarf [A] 3 x 400V + T an Drehzahlbereich	1.3	1.8	1.4	2.8	4.0
Elektrischer Bedarf [A] 3 x 230V + T an Anlasstoss	10.4	13.8	24.2	31.2	57.0
Elektrischer Bedarf [A] 3 x 230V + T an Drehzahlbereich	2.3	3.1	2.4	2.6	7.0
Dynamische Ladung [kg/cm ²]	3.1	3.5	3	3	2.5



	DEC-8	DEC-12	DEC-20	DEC-30	DEC-60
Максимальная нагрузка [кг]	8	12	20	30	57
Об/мин	1450	1450	1450	1000	1100
G - Фактор	438	493	696	408	609
Диаметр барабана [мм]	400	450	635	730	900
Высота барабана [мм]	300	350	350	350	500
Объём барабана [л]	34	42	95	120	300
Ширина [мм]	540	610	830	980	1350
Глубина [мм]	750	800	990	1150	1740
Высота [мм]	800	1000	1000	1050	1000
Вес нетто [кг]	95	144	295	360	1200
Вес брутто [кг]	110	164	330	400	1300
Объём [м ³]	0.44	0.64	1.32	1.64	2.85
Двигатель центрифуги [кВт]	1.1	2.2	4.0	5.5	7.5
Потребление электроэнергии [А] 3 x 400V + T в начале	6.0	8.0	14.0	30.0	33
Потребление электроэнергии [А] 3 x 400V + T на скорости	1.3	1.8	1.4	2.8	4.0
Потребление электроэнергии [А] 3 x 230V + T в начале	10.4	13.8	24.2	31.2	57.0
Потребление электроэнергии [А] 3 x 230V + T на скорости	2.3	3.1	2.4	2.6	7.0
Динамическая нагрузка [кг/см ²]	3.1	3.5	3	3	2.5



	DEC-8	DEC-12	DEC-20	DEC-30	DEC-60
Charge max [kg]	8	12	20	30	57
Tour par minute [r.p.m.]	1450	1450	1450	1000	1100
Facteur G	438	493	696	408	609
Diamètre Tambour [mm]	400	450	635	730	900
Auteur Tambour [mm]	300	350	350	350	500
Volume Tambour [litri]	34	42	95	120	300
Largeur [mm]	540	610	830	980	1350
Profondeur [mm]	750	800	990	1150	1740
Auteur [mm]	800	1000	1000	1050	1000
Poids net [kg]	95	144	295	360	1200
Poids brut [kg]	110	164	330	400	1300
Volume [m ³]	0.44	0.64	1.32	1.64	2.85
Moteur actionnement [kW]	1.1	2.2	4.0	5.5	7.5
Absorption électrique [A] 3 x 400V + T départ	6.0	8.0	14.0	30.0	33
Absorption électrique [A] 3 x 400V + T régime	1.3	1.8	1.4	2.8	4.0
Absorption électrique [A] 3 x 230V + T départ	10.4	13.8	24.2	31.2	57.0
Absorption électrique [A] 3 x 230V + T régime	2.3	3.1	2.4	2.6	7.0
Charge dynamique [kg/cm ²]	3.1	3.5	3	3	2.5

