



MOD : E60/SF3T-N

Production code : F60/30SPE/T

03/2024

series function 600**type** scaldapatate/heated chip dumps**model** FU 60/... SPE...

FU 60/30 SPE



Descrizione generale

Piano di lavoro realizzato in AISI 304 di spessore 10/10. Bacinella asportabile GN 1/1 e falsofondo realizzati in acciaio inox. Riscaldamento tramite resistenza in ceramica a raggi infrarossi. Interruttore generale e lampada spia di segnalazione del corretto funzionamento.

+ Plus costruttivi

- Tutto realizzato in acciaio inox
- Riscaldamento tramite resistenza in ceramica a raggi infrarossi

+ Plus prestazionali

- Bacinella asportabile GN 1/1 h 15 cm
- Apparecchiatura dal minimo ingombro (profondità 65 cm, modello da banco)

General description

Working top made of stainless steel AISI 304, 10/10 thickness. Removable container GN 1/1 and false bottom made of stainless steel. Heating by infrared ceramic over head heating element. On/Off switch and pilot light indicating power on.

+ Construction plus

- Appliance completely made in stainless steel
- Heating by infrared ceramic over head heating element

+ Performance plus

- Removable container GN 1/1 h 15 cm
- Space-saving appliance (depth 65 cm, top version model)

series function 600

type scaldapatate/heated chip dumps

model FU 60/... SPE...

dati tecnici technical data

	dimensioni <i>dimensions</i>	potenza ele. tot. <i>total ele. power</i>	sezione cavo <i>cable section</i>	assorbimento <i>absorption</i>
	<i>cm LxWxH</i>	<i>kW</i>	<i>mm</i>	<i>A</i>
FU 60/30 SPE	30x60x28 h	1 kW 220-240V 1N 50-60Hz	3G1	4,5A

series function 600

type scaldapatate/heated chip dumps

model FU 60/... SPE...

schema d'installazione installation diagram

