



MOD : TA-90/IVAC

Production code : Aura 42+ + PIL/Aura 42+

05/2025

Technical information

TA-90/IVAC



Characteristics

- With one sealing bar as standard (front)
- With double seal as standard (two sealing wires)
- Optional at no extra cost: Cut-off/wide seal
- Pump maintenance and cleaning program
- Standard Liquid control
- I-Vac: Intelligent vacuum-packing with advanced software
 - easy product selection
 - fast access of frequently used functions and programmes
- Standard soft air
- Stainless steel casing and transparent lid
- Supplied with two insert plates for a faster cycle and good positioning

Options

- Gas Flush / MAP packaging

Accessories

- Inclined insert plate (for packing liquids)
- Thermal laser printer
- External adapter
- Maintenance set for standard maintenance
- Trolley with shelves



Specs	TA-90/IVAC
Chamber LxWxH (mm)	370x420x180
Machine LxWxH (mm)	523x491x464
Voltage	230 / 1N 50-60Hz
Pump capacity 50 Hz/60 Hz (m3)	21 / 25
Machine cycle 50 Hz/60 Hz (sec.)	12-33 / 11 - 29
Power (kW)	0,8 - 1,0
Weight (kg)	61
Net seal length (mm)	410
Standard sealing bar configuration	

Dimensions mm

