



SALADETTE ▶ GN1/1 ▶ STAINLESS STEEL TOP



GENERAL FEATURES

| GN1/1 Refrigerated saladette (STAINLESS STEEL TOP) | • |
|--|---|
| Stainless Steel exterior and interior | • |
| Static Cooling | • |
| Automatic compressor cycle defrost | • |
| Foaming Agent Cyclopentane (45mm per side) | • |
| Digital Thermostat | • |
| Sliding engine room for a manageble after sales servicing | • |
| Anti-condensation thermal-braker on door frame | • |
| Easy removable condenser filter | • |
| Separated plastic water tray | • |
| Front panel tilted holes for better air circulation | • |
| Adjustable shelves GN1/1: 2 Pcs | • |
| Self closing door (New inner embossed design for a better sealing) | • |
| Removable Gasket | • |
| Engine room lock fitted as standard | • |
| N.2 Adjustable feet in the front + N.4 fix rollers | • |
| Energy efficiency class: C | • |
| | |

TECHNICAL SPECIFICATIONS

| Capacity | 214L |
|----------------------------------|--------------|
| Temperature | +0° ~ +8°C |
| Consumption | 2.2 kWh/24h |
| Rated Power | 142.4 W |
| Noise level | 50 dB(A) |
| Net Weight | 70 Kg |
| Gross Weight | 89 Kg |
| External Dimensions (WxDxH mm) | 900x700x880 |
| Internal Dimensions (WxDxH mm) | 810x586x492 |
| Packaging dimensions (WxDxH mm) | 950x750x1040 |
| Loading quantities 20'/40'/40'HQ | 36/72/72 |

CERTIFICATION





















DETAILS







Curved edge for easy cleaning



Engine room lock fitted as standard



Anti-condensation themal-braker on door frame



Inner embossed door design for a better sealing



to pull out for manageble after sales servicing



Inner assistance fan



Door design

PRODUCT DIMENSIONS



