



ABS | Upright Cabinets

REFRIGERATED UPRIGHT ► GLASS DOOR ► INOX



GENERAL FEATURES

200 Lt. Refrigerated upright (GLASS DOOR)	•
S/S external cabinet, thermoformed internally	•
Roll-bond evaporator system with fan assisted cooling	•
Automatic compressor cycle defrost	•
Foaming Agent Cyclopentane (50mm per side)	•
Digital Thermostat and internal LED light	•
High temperature alarm	•
Removable Gasket	•
Reversible door	•
Lock and main switch fitted as standard	•
Adjustable shelves: 2 Pcs + 1 Pcs Bottom	•
N.2 Adjustable feet + N.2 Rollers at the back	•
Stainless steel external handle	•
Energy efficiency class: A	•

TECHNICAL SPECIFICATIONS

Capacity	200 L
Temperature	+2°C ~ +8°C
Consumption	1.036 kWh/24h
Rated Power	60 W
Noise level	40 dB(A)
Net Weight	46.2 Kg
Gross Weight	50.5 Kg
External Dimensions (WxDxH mm)	598x679x838
Internal Dimensions (WxDxH mm)	477x443x652
Packaging dimensions (WxDxH mm)	650x680x880
Loading quantities 20'/40'/40'HQ	48/108/162

CERTIFICATION





RoHS

WR-PG21-XG













DETAILS









External cylindric handle in stainless steel (Steel color for X Version)

PRODUCT DIMENSIONS



