



ABS | Upright Cabinets

REFRIGERATED UPRIGHT ► GLASS DOOR ► INOX



GENERAL FEATURES

600 Lt. Refrigerated upright (GLASS DOOR)	•
Gray external cabinet, thermoformed internally	•
Roll-bond evaporator system with fan assisted cooling	•
Automatic compressor cycle defrost	•
Foaming Agent Cyclopentane (60mm per side)	•
Digital Thermostat	•
Removable Gasket	•
Double tempered glass with Low-e (Low emissivity glasses) and Argon	gas•
Reversible door	•
Inner horizontal LED light	•
Door with vertical cylindrical handle	•
Doors lock fitted as standard	•
Adjustable shelves: 4 Pcs + 1 BOTTOM Shelf	•
N.2 Adjustable feet + N.2 Rollers at the back	•
Energy efficiency class: B	•

TECHNICAL SPECIFICATIONS

Capacity	600 L
Temperature	M1 (-1°C~+5°C)
Consumption	2.69 kWh/24h
Rated Power	200 W
Noise level	58 dB(A)
Net Weight	104 Kg
Gross Weight	116 Kg
External Dimensions (WxDxH mm)	780x768x1890
Internal Dimensions (WxDxH mm)	660x585x1680
Packaging dimensions (WxDxH mm)	812x757x2030
Loading quantities 20'/40'/40'HQ	21/42/42

CERTIFICATION




RoHS

WR-PG61-XG



DETAILS



PRODUCT DIMENSIONS

