Mod: VCM/ND

Production code: 0620703



LYNX SERIES

UNIVERSAL TROLLEY



- Dimensions (l x w x h) 570 x 480 x 610 mm
- Swivel castors lock & brake
- Extended mobility
- · Labels and pouches storage
- Optimal use of space



LYNX SERIES

INNOVATIVE AND INTELLIGENT VACUUMPACKAGING MACHINES WITH WORLD WIDE REPUTATION

- High quality compact table models
- Pure and attractive Design
- Intelligent full colour Control Interface
- Extensive packaging parameters for specific packaging requirements
- Full HACCP compatible with labelling device
- · Easy clean concept

FOOD PRODUCTS

Retail Trade - Restaurants - Catering - Supermarkets (meat, poultry, fish, cheese, vegetables etc.)

- No contamination or bacteria's multiplication, hence an extended shelf life resulting in:
 - cost savings (larger purchasing orders, efficient cooking time spreading and diminution of products losses)
 - turnover increase (more variation and spread in product range)
- Optimal product and storage hygiene (hermetically sealed)
- No loss of product (prevents drying out, moulds and freeze burn)
- Improved product quality (product maturing in packaging, no loss of aroma)
- Professional product presentation
- Optimal packaging contributes to food safety and HACCP standards
- Ideal for Sous-vide Cuisine applications

NON-FOOD PRODUCTS

Electronics - Semi-conductors - Metal - Pharmaceutical Products - Textiles - Laboratories etc.

- Moisture free packaging
- Air and dust free packaging
- Volume reducing packaging
- Scrapes and scratches free solution
- Fraud resistant packaging
- Sterile and contamination free packaging







SPECIFICATIONS

GENERAL

- Compact Table top model
- Innovative Intelligent Design
- High volume transparent lid
- Easy clean flat working plate
- Removable wireless sealing bars
- Insert plates for fast cycle and product adjustment
- Full colour wide screen
- User friendly interface
- 6 languages operational mode
- 20 programs adjustable in % and mbar/ hPa
- USB port for data transfer
- Printing and Labelling function
- Service data storage
- Program access security
- In compliance with HACCP regulations

PACKAGING FUNCTIONS

- Vacuum
- Optimal final vacuum 99,80% (2 mbar)
- Gas-flush

Injecting food-gas for product protection and longer shelf life

- Soft-air
- Controlled ventilation for protection of product and packaging

SEALING SYSTEMS

- Double Seal
- 2 x 3,5 mm convex sealing wires for product remains elimination and strong hermetic seals.
- Cut-off sea
- 1 x 3.5 mm convex sealing wire + 1 x 1.1 mm round cutting wire / One time setting (cut off remaining flap)
- 1-2 Cut-off seal
- 1 x 3.5 mm convex sealing wire + 1 x 1.1 mm round cutting wire / Independent time setting (shrink bags)
- Wide Seal
- 1 x 8.0 mm flat sealing wire

CONTROL FUNCTIONS

• Sensor Control

Set percentage or pressure for vacuum and gas functions for accurate and constant packaging results /Automatic programming / 20 default programs / Vacuum plus time / Red meat device / Sequential vacuum

Quick stop H2O Sensor Control

Set percentage pressure for vacuum and detect boiling point of the product. For fast cycle and better food protection Automatic programming / 20 default programs / Vacuum plus time / Red meat device / Sequential vacuum

SUPPORT CONTROL FUNCTIONS

- STOP button for full cycle interruption
- Digital maintenance program for pump / Operating hours counter / Service indicator program

ACCESSORIE

- Compact label printer (Zebra Technologies)
- Inclined insert plate for packaging liquid products
- Service kit for standard maintenance
- Trolley with shelves and castors





Sentence and printing errors reserved