

09/2018

Mod: SX219G/CP9

Production code: 10307703-B-G-A



Diamond
catering equipment

Model	SX132G/CR2	SX175G/CR2	SX219G/CR2
			
Production code	10107711-B-G-A	10107712-B-G-A	10107713-B-G-A
Description	GN1/4 topping shelf with SS lid	GN1/4 topping shelf with SS lid	GN1/4 topping shelf with SS lid
Range (°C)	0° + 8°	0° + 8°	0° + 8°
Operating Mode	Static	Static	Static
External Dimensions			
Width (mm)	1320	1755	2190
Depth (mm)	324	324	324
Height (mm)	250 / 510	250 / 510	250 / 510
Internal Dimensions			
Width (mm)	837	1272	1707
Depth (mm)	243	243	243
Height (mm)	150	150	150
Gross capacity (L)	31	46	62
Defrost			
Type of defrost	No defrost	No defrost	No defrost
Compressor			
Brand	HUAYI / Cubigel	HUAYI / Cubigel	HUAYI / Cubigel
Model	NBC30RA	NBC30RA	NLY45RA_b
Power (hp)	1/10	1/10	1/5
Cooling power (W)	237	237	357
Evaporation temp. (°C)	-10 / +45	-10 / +45	-10 / +45
Climate class (°C)	4	4	4
Refrigerant			
Refrigerant fluid / GWP	R290 / 3	R290 / 3	R290 / 3
Refrigerant charge (kg)	0,090	0,090	0,100
Electronic Controller			
Brand	Dixell	Dixell	Dixell
Model	XR20CH	XR20CH	XR20CH
Electrical			
Power input (W/A)	135 / 1,1	135 / 1,1	190 / 1,0
Power supply (V/Hz)	220-240/50	220-240/50	220-240/50
220V/60Hz	no	no	no
Packaging Details			
Packed volume (m³)	0,18	0,24	0,29
Gross weight (kg)	44	54	65
Net weight (kg)	32	39	46