

09/2018

Mod: SY249G/PP9

Production code: 10309714-B-G-0



Diamond
catering equipment

Model	SY160G/PR2	SY198G/PR2	SY249G/PR2
			
Production code	10107719-B-G-0	10107716-B-G-0	10107717-B-G-0
Description	GN1/3 topping shelf with glass top	GN1/3 topping shelf with glass top	GN1/3 topping shelf with glass top
Range (°C)	0° + 8°	0° + 8°	0° + 8°
Operating Mode	Static	Static	Static
External Dimensions			
Width (mm)	1600	1980	2490
Depth (mm)	384	384	384
Height (mm)	387	387	387
Internal Dimensions			
Width (mm)	1117	1497	2007
Depth (mm)	303	303	303
Height (mm)	150	150	150
Gross capacity (L)	51	68	91
Defrost			
Type of defrost	No defrost	No defrost	No defrost
Compressor			
Brand	HUAYI / Cubigel	HUAYI / Cubigel	HUAYI / Cubigel
Model	NBC30RA	NBC30RA	NLY45RA_b
Power (hp)	1/10	1/10	1/5
Cooling power (W)	237	237	357
Evaporation temp. (°C)	-10 / +45	-10 / +45	-10 / +45
Climate class (°C)	4	4	4
Refrigerant			
Refrigerant fluid / GWP	R290 / 3	R290 / 3	R290 / 3
Refrigerant charge (kg)	0,090	0,090	0,100
Electronic Controller			
Brand	Dixell	Dixell	Dixell
Model	XR20CH	XR20CH	XR20CH
Electrical			
Power input (W/A)	135 / 1,1	135 / 1,1	190 / 1,0
Power supply (V/Hz)	220-240/50	220-240/50	220-240/50
220V/60Hz	no	no	no
Packaging Details			
Packed volume (m³)	0,27	0,33	0,43
Gross weight (kg)	69	77	100
Net weight (kg)	55	62	82