

10/2017

Mod: DRW18-TS/D

Production code: R18DDIELS8AIA



Diamond
catering equipment

Low spin washing machine RC 18

C030911C

Technical data

Capacity	18	kg
Drum diameter	700	mm
Drum depth	470	mm
Drum volume	180	l
Load diameter	380	mm
Wash speed	37	rpm
Low speed	470	rpm
G Factor	86	
Noise	65	dB(A)
Heating leaks from the structure**	5	%

Weights and packing dimension

Height	1640	mm
Width	1000	mm
Depth	1150	mm
Volum	2	m ³
Gross weight	317	kg
Net weight	277	kg

Water consumpt

Total consumption	297	litri
Low level	66	litri
High level	75	litri

Electrical heating

Heating element	3 x 4000	W
Consumption*	7	kWh

Steam heating

Steam consumption*	11	kg
Max pressure***	4,5	bar





* Cycle B - ISO 9398

** Percentage on installed power


*** Optional 10 bar

Power and absorptions

Heating	Supply	Total power	Absorption
Elettrico	3ph 400V+N	14 kW	22 A
Elettrico	3ph 230V	14 kW	38 A
Elettrico	1ph 230V	14 kW	66 A
Vapore/Hot Water	3ph 400V+N	- kW	- A
Vapore/Hot Water	3ph 230V	1,5 kW	4 A
Vapore/Hot Water	1ph 230V	1,5 kW	4 A




DISTANCE BETWEEN
FIXING BOLTS



FRONT

BETON BASE



- 1 - Cold water inlet 3/4" - Press 0,5 ÷ 10 bar
- 2 - Hot water inlet 3/4" - Press 0,5 ÷ 10 bar
- 3 - Steam inlet 3/4"
- 4 - Drain Ø50 mm

- 5 - Bleed
- 6 - Electrical power
- 7 - External connections
- 8 - Fuse